

NAME

ASN1_item_d2i_ex, ASN1_item_d2i, ASN1_item_d2i_bio_ex, ASN1_item_d2i_bio,
ASN1_item_d2i_fp_ex, ASN1_item_d2i_fp, ASN1_item_i2d_mem_bio - decode and encode
DER-encoded ASN.1 structures

SYNOPSIS

```
#include <openssl/asn1.h>
```

```
ASN1_VALUE *ASN1_item_d2i_ex(ASN1_VALUE **pval, const unsigned char **in,  
                             long len, const ASN1_ITEM *it,  
                             OSSL_LIB_CTX *libctx, const char *propq);
```

```
ASN1_VALUE *ASN1_item_d2i(ASN1_VALUE **pval, const unsigned char **in,  
                           long len, const ASN1_ITEM *it);
```

```
void *ASN1_item_d2i_bio_ex(const ASN1_ITEM *it, BIO *in, void *x,  
                           OSSL_LIB_CTX *libctx, const char *propq);
```

```
void *ASN1_item_d2i_bio(const ASN1_ITEM *it, BIO *in, void *x);
```

```
void *ASN1_item_d2i_fp_ex(const ASN1_ITEM *it, FILE *in, void *x,  
                           OSSL_LIB_CTX *libctx, const char *propq);
```

```
void *ASN1_item_d2i_fp(const ASN1_ITEM *it, FILE *in, void *x);
```

```
BIO *ASN1_item_i2d_mem_bio(const ASN1_ITEM *it, const ASN1_VALUE *val);
```

DESCRIPTION

ASN1_item_d2i_ex() decodes the contents of the data stored in *in* of length *len* which must be a DER-encoded ASN.1 structure, using the ASN.1 template *it*. It places the result in *pval* unless *pval* is NULL. If *pval* is non-NULL on entry then the **ASN1_VALUE** present there will be reused. Otherwise a new **ASN1_VALUE** will be allocated. If any algorithm fetches are required during the process then they will use the **OSSL_LIB_CTX** provided in the *libctx* parameter and the property query string in *propq*. See "ALGORITHM FETCHING" in **crypto(7)** for more information about algorithm fetching. On exit *in* will be updated to point to the next byte in the buffer after the decoded structure.

ASN1_item_d2i() is the same as **ASN1_item_d2i_ex()** except that the default **OSSL_LIB_CTX** is used (i.e. NULL) and with a NULL property query string.

ASN1_item_d2i_bio_ex() decodes the contents of its input BIO *in*, which must be a DER-encoded ASN.1 structure, using the ASN.1 template *it* and places the result in *pval* unless *pval* is NULL. If *in* is NULL it returns NULL, else a pointer to the parsed structure. If any algorithm fetches are required during the process then they will use the **OSSL_LIB_CTX** provided in the *libctx* parameter and the

property query string in *propq*. See "ALGORITHM FETCHING" in **crypto(7)** for more information about algorithm fetching.

ASN1_item_d2i_bio() is the same as **ASN1_item_d2i_bio_ex()** except that the default **OSSL_LIB_CTX** is used (i.e. NULL) and with a NULL property query string.

ASN1_item_d2i_fp_ex() is the same as **ASN1_item_d2i_bio_ex()** except that a FILE pointer is provided instead of a BIO.

ASN1_item_d2i_fp() is the same as **ASN1_item_d2i_fp_ex()** except that the default **OSSL_LIB_CTX** is used (i.e. NULL) and with a NULL property query string.

ASN1_item_i2d_mem_bio() encodes the given ASN.1 value *val* using the ASN.1 template *it* and returns the result in a memory BIO.

RETURN VALUES

ASN1_item_d2i_bio() returns a pointer to an **ASN1_VALUE** or NULL.

ASN1_item_i2d_mem_bio() returns a pointer to a memory BIO or NULL on error.

HISTORY

The functions **ASN1_item_d2i_ex()**, **ASN1_item_d2i_bio_ex()**, **ASN1_item_d2i_fp_ex()** and **ASN1_item_i2d_mem_bio()** were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.