

NAME

ERR_new, ERR_set_debug, ERR_set_error, ERR_vset_error - Error recording building blocks

SYNOPSIS

```
#include <openssl/err.h>
```

```
void ERR_new(void);
void ERR_set_debug(const char *file, int line, const char *func);
void ERR_set_error(int lib, int reason, const char *fmt, ...);
void ERR_vset_error(int lib, int reason, const char *fmt, va_list args);
```

DESCRIPTION

The functions described here are generally not used directly, but rather through macros such as **ERR_raise**(3). They can still be useful for anyone that wants to make their own macros.

ERR_new() allocates a new slot in the thread's error queue.

ERR_set_debug() sets the debug information related to the current error in the thread's error queue. The values that can be given are the filename *file*, line in the file *line* and the name of the function *func* where the error occurred. The names must be constant, this function will only save away the pointers, not copy the strings.

ERR_set_error() sets the error information, which are the library number *lib* and the reason code *reason*, and additional data as a format string *fmt* and an arbitrary number of arguments. The additional data is processed with **BIO_snprintf**(3) to form the additional data string, which is allocated and store in the error record.

ERR_vset_error() works like **ERR_set_error**(), but takes a **va_list** argument instead of a variable number of arguments.

RETURN VALUES

ERR_new, ERR_set_debug, ERR_set_error and ERR_vset_error do not return any values.

NOTES

The library number is unique to each unit that records errors. OpenSSL has a number of preallocated ones for its own uses, but others may allocate their own library number dynamically with **ERR_get_next_error_library**(3).

Reason codes are unique within each library, and may have an associated set of strings as a short description of the reason. For dynamically allocated library numbers, reason strings are recorded with

ERR_load_strings(3).

Provider authors are supplied with core versions of these functions, see **provider-base(7)**.

SEE ALSO

ERR_raise(3), ERR_get_next_error_library(3), ERR_load_strings(3), BIO_snprintf(3), provider-base(7)

COPYRIGHT

Copyright 2000-2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.