

NAME

EVP_PKEY_print_public, EVP_PKEY_print_private, EVP_PKEY_print_params,
EVP_PKEY_print_public_fp, EVP_PKEY_print_private_fp, EVP_PKEY_print_params_fp - public
key algorithm printing routines

SYNOPSIS

```
#include <openssl/evp.h>

int EVP_PKEY_print_public(BIO *out, const EVP_PKEY *pkey,
                          int indent, ASN1_PCTX *pctx);
int EVP_PKEY_print_public_fp(FILE *fp, const EVP_PKEY *pkey,
                              int indent, ASN1_PCTX *pctx);
int EVP_PKEY_print_private(BIO *out, const EVP_PKEY *pkey,
                            int indent, ASN1_PCTX *pctx);
int EVP_PKEY_print_private_fp(FILE *fp, const EVP_PKEY *pkey,
                               int indent, ASN1_PCTX *pctx);
int EVP_PKEY_print_params(BIO *out, const EVP_PKEY *pkey,
                           int indent, ASN1_PCTX *pctx);
int EVP_PKEY_print_params_fp(FILE *fp, const EVP_PKEY *pkey,
                              int indent, ASN1_PCTX *pctx);
```

DESCRIPTION

The functions **EVP_PKEY_print_public()**, **EVP_PKEY_print_private()** and **EVP_PKEY_print_params()** print out the public, private or parameter components of key *pkey* respectively. The key is sent to **BIO** *out* in human readable form. The parameter *indent* indicates how far the printout should be indented.

The *pctx* parameter allows the print output to be finely tuned by using ASN1 printing options. If *pctx* is set to NULL then default values will be used.

The functions **EVP_PKEY_print_public_fp()**, **EVP_PKEY_print_private_fp()** and **EVP_PKEY_print_params_fp()** do the same as the **BIO** based functions but use **FILE** *fp* instead.

NOTES

Currently no public key algorithms include any options in the *pctx* parameter.

If the key does not include all the components indicated by the function then only those contained in the key will be printed. For example passing a public key to **EVP_PKEY_print_private()** will only print the public components.

RETURN VALUES

These functions all return 1 for success and 0 or a negative value for failure. In particular a return value of -2 indicates the operation is not supported by the public key algorithm.

SEE ALSO

EVP_PKEY_CTX_new(3), **EVP_PKEY_keygen(3)**

HISTORY

The functions **EVP_PKEY_print_public()**, **EVP_PKEY_print_private()**, and **EVP_PKEY_print_params()** were added in OpenSSL 1.0.0.

The functions **EVP_PKEY_print_public_fp()**, **EVP_PKEY_print_private_fp()**, and **EVP_PKEY_print_params_fp()** were added in OpenSSL 3.0.

COPYRIGHT

Copyright 2006-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.