

**NAME**

MagickWand-config - get information about the installed version of the Magick Wand

**SYNOPSIS**

**MagickWand-config** [**--cflags**] [**--cppflags**] [**--exec-prefix**] [**--ldflags**] [**--libs**] [**--prefix**] [**--version**]

**DESCRIPTION**

**MagickWand-config** prints the compiler and linker flags required to compile and link programs that use the **Wand** Application Programmer Interface.

**EXAMPLES**

To print the version of the installed distribution of **Wand**, use:

```
MagickWand-config --version
```

To compile a program that calls the **Wand** Application Programmer Interface, use:

```
cc `MagickWand-config --cflags --cppflags --ldflags --libs` program.c
```

**OPTIONS****--cflags**

Print the compiler flags that were used to compile **libWand**.

**--cppflags**

Print the preprocessor flags that are needed to find the **Wand** C include files and defines to ensure that the Wand data structures match between your program and the installed libraries.

**--exec-prefix**

Print the directory under which target specific binaries and executables are installed.

**--ldflags**

Print the linker flags that are needed to link with the **Wand** library.

**--libs**

Print the linker flags that are needed to link a program with **libWand**.

**--version**

Print the version of the **Wand** distribution to standard output.

**COPYRIGHT**

See <http://imagemagick.org/script/license.php>

**AUTHORS**

Cristy, ImageMagick Studio LLC