

NAME

OSSL_STORE_expect, OSSL_STORE_supports_search, OSSL_STORE_find - Specify what object type is expected

SYNOPSIS

```
#include <openssl/store.h>
```

```
int OSSL_STORE_expect(OSSL_STORE_CTX *ctx, int expected_type);
```

```
int OSSL_STORE_supports_search(OSSL_STORE_CTX *ctx, int criterion_type);
```

```
int OSSL_STORE_find(OSSL_STORE_CTX *ctx, OSSL_STORE_SEARCH *search);
```

DESCRIPTION

OSSL_STORE_expect() helps applications filter what **OSSL_STORE_load()** returns by specifying a **OSSL_STORE_INFO** type. By default, no expectations on the types of objects to be loaded are made. *expected_type* may be 0 to indicate explicitly that no expectation is made, or it may be any of the known object types (see "SUPPORTED OBJECTS" in **OSSL_STORE_INFO(3)**) except for **OSSL_STORE_INFO_NAME**. For example, if "file:/foo/bar/store.pem" contains several objects of different type and only certificates are interesting, the application can simply say that it expects the type **OSSL_STORE_INFO_CERT**.

OSSL_STORE_find() helps applications specify a criterion for a more fine grained search of objects.

OSSL_STORE_supports_search() checks if the loader of the given OSSL_STORE context supports the given search type. See "SUPPORTED CRITERION TYPES" in **OSSL_STORE_SEARCH(3)** for information on the supported search criterion types.

OSSL_STORE_expect() and **OSSL_STORE_find** *must* be called before the first **OSSL_STORE_load()** of a given session, or they will fail.

NOTES

If a more elaborate filter is required by the application, a better choice would be to use a post-processing function. See **OSSL_STORE_open(3)** for more information.

However, some loaders may take advantage of the knowledge of an expected type to make object retrieval more efficient, so if a single type is expected, this method is usually preferable.

RETURN VALUES

OSSL_STORE_expect() returns 1 on success, or 0 on failure.

OSSL_STORE_supports_search() returns 1 if the criterion is supported, or 0 otherwise.

OSSL_STORE_find() returns 1 on success, or 0 on failure.

SEE ALSO

ossl_store(7), **OSSL_STORE_INFO(3)**, **OSSL_STORE_SEARCH(3)**, **OSSL_STORE_load(3)**

HISTORY

OSSL_STORE_expect(), **OSSL_STORE_supports_search()** and **OSSL_STORE_find()** were added in OpenSSL 1.1.1.

COPYRIGHT

Copyright 2018-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.