

NAME

PKCS12_SAFEBAG_get0_attr, PKCS12_SAFEBAG_get0_type, PKCS12_SAFEBAG_get_nid,
 PKCS12_SAFEBAG_get_bag_nid, PKCS12_SAFEBAG_get0_bag_obj,
 PKCS12_SAFEBAG_get0_bag_type, PKCS12_SAFEBAG_get1_cert, PKCS12_SAFEBAG_get1_crl,
 PKCS12_SAFEBAG_get0_safes, PKCS12_SAFEBAG_get0_p8inf, PKCS12_SAFEBAG_get0_pkcs8
 - Get objects from a PKCS#12 safeBag

SYNOPSIS

```
#include <openssl/pkcs12.h>
```

```
const ASN1_TYPE *PKCS12_SAFEBAG_get0_attr(const PKCS12_SAFEBAG *bag,
                                           int attr_nid);
const ASN1_OBJECT *PKCS12_SAFEBAG_get0_type(const PKCS12_SAFEBAG *bag);
int PKCS12_SAFEBAG_get_nid(const PKCS12_SAFEBAG *bag);
int PKCS12_SAFEBAG_get_bag_nid(const PKCS12_SAFEBAG *bag);
const ASN1_TYPE *PKCS12_SAFEBAG_get0_bag_obj(const PKCS12_SAFEBAG *bag);
const ASN1_OBJECT *PKCS12_SAFEBAG_get0_bag_type(const PKCS12_SAFEBAG *bag);
X509 *PKCS12_SAFEBAG_get1_cert(const PKCS12_SAFEBAG *bag);
X509_CRL *PKCS12_SAFEBAG_get1_crl(const PKCS12_SAFEBAG *bag);
const STACK_OF(PKCS12_SAFEBAG) *PKCS12_SAFEBAG_get0_safes(const PKCS12_SAFEBAG *bag);
const PKCS8_PRIV_KEY_INFO *PKCS12_SAFEBAG_get0_p8inf(const PKCS12_SAFEBAG *bag);
const X509_SIG *PKCS12_SAFEBAG_get0_pkcs8(const PKCS12_SAFEBAG *bag);
```

DESCRIPTION

PKCS12_SAFEBAG_get0_attr() gets the attribute value corresponding to the **attr_nid**.

PKCS12_SAFEBAG_get0_type() gets the **safeBag** type as an OID, whereas

PKCS12_SAFEBAG_get_nid() gets the **safeBag** type as an NID, which could be **NID_certBag**,

NID_crlBag, **NID_keyBag**, **NID_secretBag**, **NID_safeContentsBag** or **NID_pkcs8ShroudedKeyBag**.

PKCS12_SAFEBAG_get_bag_nid() gets the type of the object contained within the

PKCS12_SAFEBAG. This corresponds to the bag type for most bags, but can be arbitrary for **secretBags**. **PKCS12_SAFEBAG_get0_bag_type()** gets this type as an OID.

PKCS12_SAFEBAG_get0_bag_obj() retrieves the object contained within the **safeBag**.

PKCS12_SAFEBAG_get1_cert() and **PKCS12_SAFEBAG_get1_crl()** return new **X509** or **X509_CRL** objects from the item in the **safeBag**.

PKCS12_SAFEBAG_get0_p8inf() and **PKCS12_SAFEBAG_get0_pkcs8()** return the PKCS8 object

from a PKCS8shroudedKeyBag or a keyBag.

PKCS12_SAFEBAG_get0_safes() retrieves the set of **safeBags** contained within a safeContentsBag.

RETURN VALUES

PKCS12_SAFEBAG_get_nid() and **PKCS12_SAFEBAG_get_bag_nid()** return the NID of the safeBag or bag object, or -1 if there is no corresponding NID. Other functions return a valid object of the specified type or NULL if an error occurred.

SEE ALSO

PKCS12_create(3), **PKCS12_add_safe(3)**, **PKCS12_add_safes(3)**

COPYRIGHT

Copyright 2019-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.