

NAME

PKCS7_sign_add_signer, PKCS7_add_certificate, PKCS7_add_crl - add information to PKCS7 structure

SYNOPSIS

```
#include <openssl/pkcs7.h>
```

```
PKCS7_SIGNER_INFO *PKCS7_sign_add_signer(PKCS7 *p7, X509 *sigcert,  
                                           EVP_PKEY *pkey, const EVP_MD *md, int flags);  
int PKCS7_add_certificate(PKCS7 *p7, X509 *cert);  
int PKCS7_add_crl(PKCS7 *p7, X509_CRL *crl);
```

DESCRIPTION

PKCS7_sign_add_signer() adds a signer with certificate *sigcert* and private key *pkey* using message digest *md* to a PKCS7 signed data structure *p7*.

The **PKCS7** structure should be obtained from an initial call to **PKCS7_sign()** with the flag **PKCS7_PARTIAL** set or in the case of re-signing a valid PKCS#7 signed data structure.

If the *md* parameter is NULL then the default digest for the public key algorithm will be used.

Unless the **PKCS7_REUSE_DIGEST** flag is set the returned **PKCS7** structure is not complete and must be finalized either by streaming (if applicable) or a call to **PKCS7_final()**.

NOTES

The main purpose of this function is to provide finer control over a PKCS#7 signed data structure where the simpler **PKCS7_sign()** function defaults are not appropriate. For example if multiple signers or non default digest algorithms are needed.

Any of the following flags (ored together) can be passed in the *flags* parameter.

If **PKCS7_REUSE_DIGEST** is set then an attempt is made to copy the content digest value from the **PKCS7** structure: to add a signer to an existing structure. An error occurs if a matching digest value cannot be found to copy. The returned **PKCS7** structure will be valid and finalized when this flag is set.

If **PKCS7_PARTIAL** is set in addition to **PKCS7_REUSE_DIGEST** then the **PKCS7_SIGNER_INFO** structure will not be finalized so additional attributes can be added. In this case an explicit call to **PKCS7_SIGNER_INFO_sign()** is needed to finalize it.

If **PKCS7_NOCERTS** is set the signer's certificate will not be included in the **PKCS7** structure, the

signer's certificate must still be supplied in the *signcert* parameter though. This can reduce the size of the signature if the signers certificate can be obtained by other means: for example a previously signed message.

The signedData structure includes several PKCS#7 authenticatedAttributes including the signing time, the PKCS#7 content type and the supported list of ciphers in an SMIMECapabilities attribute. If **PKCS7_NOATTR** is set then no authenticatedAttributes will be used. If **PKCS7_NOSMIMECAP** is set then just the SMIMECapabilities are omitted.

If present the SMIMECapabilities attribute indicates support for the following algorithms: triple DES, 128 bit RC2, 64 bit RC2, DES and 40 bit RC2. If any of these algorithms is disabled then it will not be included.

PKCS7_sign_add_signers() returns an internal pointer to the **PKCS7_SIGNER_INFO** structure just added, which can be used to set additional attributes before it is finalized.

PKCS7_add_certificate() adds to the **PKCS7** structure *p7* the certificate *cert*, which may be an end-entity (signer) certificate or a CA certificate useful for chain building. This is done internally by **PKCS7_sign_ex(3)** and similar signing functions. It may have to be used before calling **PKCS7_verify(3)** in order to provide any missing certificate(s) needed for verification.

PKCS7_add_crl() adds the CRL *crl* to the **PKCS7** structure *p7*. This may be called to provide certificate status information to be included when signing or to use when verifying the **PKCS7** structure.

RETURN VALUES

PKCS7_sign_add_signers() returns an internal pointer to the **PKCS7_SIGNER_INFO** structure just added or NULL if an error occurs.

PKCS7_add_certificate() and **PKCS7_add_crl()** return 1 on success, 0 on error.

SEE ALSO

ERR_get_error(3), **PKCS7_sign_ex(3)**, **PKCS7_final(3)**, **PKCS7_verify(3)**

HISTORY

The **PKCS7_sign_add_signer()** function was added in OpenSSL 1.0.0.

COPYRIGHT

Copyright 2007-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.