

NAME

RAND_set_rand_method, RAND_get_rand_method, RAND_OpenSSL - select RAND method

SYNOPSIS

```
#include <openssl/rand.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining **OPENSSL_API_COMPAT** with a suitable version value, see **openssl_user_macros(7)**:

```
RAND_METHOD *RAND_OpenSSL(void);
```

```
int RAND_set_rand_method(const RAND_METHOD *meth);
```

```
const RAND_METHOD *RAND_get_rand_method(void);
```

DESCRIPTION

All of the functions described on this page are deprecated. Applications should instead use **RAND_set_DRBG_type(3)**, **EVP_RAND(3)** and **EVP_RAND(7)**.

A **RAND_METHOD** specifies the functions that OpenSSL uses for random number generation.

RAND_OpenSSL() returns the default **RAND_METHOD** implementation by OpenSSL. This implementation ensures that the PRNG state is unique for each thread.

If an **ENGINE** is loaded that provides the RAND API, however, it will be used instead of the method returned by **RAND_OpenSSL()**. This is deprecated in OpenSSL 3.0.

RAND_set_rand_method() makes **meth** the method for PRNG use. If an **ENGINE** was providing the method, it will be released first.

RAND_get_rand_method() returns a pointer to the current **RAND_METHOD**.

THE RAND_METHOD STRUCTURE

```
typedef struct rand_meth_st {
    int (*seed)(const void *buf, int num);
    int (*bytes)(unsigned char *buf, int num);
    void (*cleanup)(void);
    int (*add)(const void *buf, int num, double entropy);
    int (*pseudorand)(unsigned char *buf, int num);
    int (*status)(void);
};
```

RAND_SET_RAND_METHOD(3ossl) OpenSSL RAND_SET_RAND_METHOD(3ossl)

```
} RAND_METHOD;
```

The fields point to functions that are used by, in order, **RAND_seed()**, **RAND_bytes()**, internal RAND cleanup, **RAND_add()**, **RAND_pseudo_rand()** and **RAND_status()**. Each pointer may be NULL if the function is not implemented.

RETURN VALUES

RAND_set_rand_method() returns 1 on success and 0 on failure. **RAND_get_rand_method()** and **RAND_OpenSSL()** return pointers to the respective methods.

SEE ALSO

EVP RAND(3), **RAND_set_DRBG_type(3)**, **RAND_bytes(3)**, **ENGINE_by_id(3)**, **EVP RAND(7)**, **RAND(7)**

HISTORY

All of these functions were deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.