

NAME

SSL_CTX_flush_sessions - remove expired sessions

SYNOPSIS

```
#include <openssl/ssl.h>
```

```
void SSL_CTX_flush_sessions(SSL_CTX *ctx, long tm);
```

DESCRIPTION

SSL_CTX_flush_sessions() causes a run through the session cache of **ctx** to remove sessions expired at time **tm**.

NOTES

If enabled, the internal session cache will collect all sessions established up to the specified maximum number (see **SSL_CTX_sess_set_cache_size()**). As sessions will not be reused ones they are expired, they should be removed from the cache to save resources. This can either be done automatically whenever 255 new sessions were established (see **SSL_CTX_set_session_cache_mode(3)**) or manually by calling **SSL_CTX_flush_sessions()**.

The parameter **tm** specifies the time which should be used for the expiration test, in most cases the actual time given by **time(0)** will be used.

SSL_CTX_flush_sessions() will only check sessions stored in the internal cache. When a session is found and removed, the **remove_session_cb** is however called to synchronize with the external cache (see **SSL_CTX_sess_set_get_cb(3)**).

RETURN VALUES

SSL_CTX_flush_sessions() does not return a value.

SEE ALSO

ssl(7), **SSL_CTX_set_session_cache_mode(3)**, **SSL_CTX_set_timeout(3)**,
SSL_CTX_sess_set_get_cb(3)

COPYRIGHT

Copyright 2001-2018 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file **LICENSE** in the source distribution or at <https://www.openssl.org/source/license.html>.