

NAME

TS_RESP_CTX_new_ex, TS_RESP_CTX_new, TS_RESP_CTX_free - Timestamp response context object creation

SYNOPSIS

```
#include <openssl/ts.h>
```

```
TS_RESP_CTX *TS_RESP_CTX_new_ex(OSSL_LIB_CTX *libctx, const char *propq);  
TS_RESP_CTX *TS_RESP_CTX_new(void);  
void TS_RESP_CTX_free(TS_RESP_CTX *ctx);
```

DESCRIPTION

Creates a response context that can be used for generating responses.

TS_RESP_CTX_new_ex() allocates and initializes a **TS_RESP_CTX** structure with a library context of *libctx* and a property query of *propq*. The library context and property query can be used to select which providers supply the fetched algorithms.

TS_RESP_CTX_new() is similar to **TS_RESP_CTX_new_ex()** but sets the library context and property query to NULL. This results in the default (NULL) library context being used for any operations requiring algorithm fetches.

TS_RESP_CTX_free() frees the **TS_RESP_CTX** object *ctx*.

RETURN VALUES

If the allocation fails, **TS_RESP_CTX_new_ex()** and **TS_RESP_CTX_new()** return NULL, otherwise it returns a pointer to the newly allocated structure.

HISTORY

The function **TS_RESP_CTX_new_ex()** was added in OpenSSL 3.0.

COPYRIGHT

Copyright 2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.