

NAME

X509_CRL_get0_by_serial, X509_CRL_get0_by_cert, X509_CRL_get_REVOKED, X509_REVOKED_get0_serialNumber, X509_REVOKED_get0_revocationDate, X509_REVOKED_set_serialNumber, X509_REVOKED_set_revocationDate, X509_CRL_add0_revoked, X509_CRL_sort - CRL revoked entry utility functions

SYNOPSIS

```
#include <openssl/x509.h>
```

```
int X509_CRL_get0_by_serial(X509_CRL *crl,
                           X509_REVOKED **ret, const ASN1_INTEGER *serial);
int X509_CRL_get0_by_cert(X509_CRL *crl, X509_REVOKED **ret, X509 *x);
```

```
STACK_OF(X509_REVOKED) *X509_CRL_get_REVOKED(X509_CRL *crl);
```

```
const ASN1_INTEGER *X509_REVOKED_get0_serialNumber(const X509_REVOKED *r);
const ASN1_TIME *X509_REVOKED_get0_revocationDate(const X509_REVOKED *r);
```

```
int X509_REVOKED_set_serialNumber(X509_REVOKED *r, ASN1_INTEGER *serial);
int X509_REVOKED_set_revocationDate(X509_REVOKED *r, ASN1_TIME *tm);
```

```
int X509_CRL_add0_revoked(X509_CRL *crl, X509_REVOKED *rev);
```

```
int X509_CRL_sort(X509_CRL *crl);
```

DESCRIPTION

X509_CRL_get0_by_serial() attempts to find a revoked entry in *crl* for serial number *serial*. If it is successful, it sets **ret* to the internal pointer of the matching entry. As a result, **ret* **MUST NOT** be freed after the call.

X509_CRL_get0_by_cert() is similar to **X509_get0_by_serial()** except it looks for a revoked entry using the serial number of certificate *x*.

X509_CRL_get_REVOKED() returns an internal pointer to a STACK of all revoked entries for *crl*.

X509_REVOKED_get0_serialNumber() returns an internal pointer to the serial number of *r*.

X509_REVOKED_get0_revocationDate() returns an internal pointer to the revocation date of *r*.

X509_REVOKED_set_serialNumber() sets the serial number of *r* to *serial*. The supplied *serial* pointer

is not used internally so it should be freed after use.

X509_REVOKED_set_revocationDate() sets the revocation date of *r* to *tm*. The supplied *tm* pointer is not used internally so it should be freed after use.

X509_CRL_add0_revoked() appends revoked entry *rev* to CRL *crl*. The pointer *rev* is used internally so it **MUST NOT** be freed after the call: it is freed when the parent CRL is freed.

X509_CRL_sort() sorts the revoked entries of *crl* into ascending serial number order.

NOTES

Applications can determine the number of revoked entries returned by **X509_CRL_get_REVOKED()** using **sk_X509_REVOKED_num()** and examine each one in turn using **sk_X509_REVOKED_value()**.

RETURN VALUES

X509_CRL_get0_by_serial() and **X509_CRL_get0_by_cert()** return 0 for failure, 1 on success except if the revoked entry has the reason "removeFromCRL" (8), in which case 2 is returned.

X509_CRL_get_REVOKED() returns a STACK of revoked entries.

X509_REVOKED_get0_serialNumber() returns an **ASN1_INTEGER** structure.

X509_REVOKED_get0_revocationDate() returns an **ASN1_TIME** structure.

X509_REVOKED_set_serialNumber(), **X509_REVOKED_set_revocationDate()**, **X509_CRL_add0_revoked()** and **X509_CRL_sort()** return 1 for success and 0 for failure.

SEE ALSO

d2i_X509(3), **ERR_get_error(3)**, **X509_get0_signature(3)**, **X509_get_ext_d2i(3)**,
X509_get_extension_flags(3), **X509_get_pubkey(3)**, **X509_get_subject_name(3)**,
X509_get_version(3), **X509_NAME_add_entry_by_txt(3)**, **X509_NAME_ENTRY_get_object(3)**,
X509_NAME_get_index_by_NID(3), **X509_NAME_print_ex(3)**, **X509_new(3)**, **X509_sign(3)**,
X509V3_get_d2i(3), **X509_verify_cert(3)**

COPYRIGHT

Copyright 2015-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.