

NAME

XtAppError, XtAppSetErrorHandler, XtAppSetWarningHandler, XtAppWarning - low-level error handlers

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
void XtAppError(XtAppContext app_context, const char *message);
```

```
XtErrorHandler XtAppSetErrorHandler(XtAppContext app_context, XtErrorHandler handler);
```

```
XtErrorHandler XtAppSetWarningHandler(XtAppContext app_context, XtErrorHandler handler);
```

```
void XtAppWarning(XtAppContext app_context, const char *message);
```

ARGUMENTS

app_context Specifies the application context.

message Specifies the nonfatal error message that is to be reported.

handler Specifies the new fatal error procedure, which should not return, or the nonfatal error procedure, which usually returns.

message Specifies the message that is to be reported.

DESCRIPTION

The **XtAppError** function calls the installed error procedure and passes the specified message.

The **XtAppSetErrorHandler** function registers the specified procedure, which is called when a fatal error condition occurs.

The **XtAppSetWarningHandler** registers the specified procedure, which is called when a nonfatal error condition occurs.

The **XtAppWarning** function calls the installed nonfatal error procedure and passes the specified message.

SEE ALSO

XtAppGetErrorDatabase(3), XtAppErrorMsg(3)

X Toolkit Intrinsics - C Language Interface

XtAppError(3)

XT FUNCTIONS

XtAppError(3)

Xlib - C Language X Interface