

NAME

XtCallCallbacks, XtCallCallbackList, XtHasCallbacks - process callbacks

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
void XtCallCallbacks(Widget w, const char *callback_name, XtPointer call_data);
```

```
void XtCallCallbackList(Widget w, XtCallbackList callbacks, XtPointer call_data);
```

```
typedef enum { XtCallbackNoList, XtCallbackHasNone, XtCallbackHasSome } XtCallbackStatus;
```

```
XtCallbackStatus XtHasCallbacks(Widget w, const char *callback_name);
```

ARGUMENTS

callback_name Specifies the callback list to be executed or checked.

call_data Specifies a callback-list specific data value to pass to each of the callback procedure in the list.

callbacks Specifies the callback list to be executed.

w Specifies the widget.

DESCRIPTION

The **XtCallCallbacks** function calls each procedure that is registered in the specified widget's callback list.

If *callbacks* is not NULL, **XtCallCallbackList** calls each of the callback procedures in the list, passing client data and *call_data*. The *callbacks* parameter must specify the contents of a widget or object resource declared with representation type **XtRCallback**.

The **XtHasCallbacks** function first checks to see if the widget has a callback list identified by *callback_name*. If the callback list does not exist, **XtHasCallbacks** returns **XtCallbackNoList**. If the callback list exists but is empty, it returns **XtCallbackHasNone**. If the callback list exists and has at least one callback registered, it returns **XtCallbackHasSome**.

SEE ALSO

XtAddCallback(3)

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface