

NAME

XtErrorMsg, XtSetErrorMsgHandler, XtWarningMsg, XtSetWarningMsgHandler - high-level error handlers

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
_X_NORETURN void XtErrorMsg(const char *name, const char *type, const char *class, const char *defaultMsg, String *params, Cardinal *num_params);
```

```
void XtSetErrorMsgHandler(_X_NORETURN XtErrorMsgHandler msg_handler);
```

```
void XtSetWarningMsgHandler(XtErrorMsgHandler msg_handler);
```

```
void XtWarningMsg(const char *name, const char *type, const char *class, const char *defaultMsg, String *params, Cardinal *num_params);
```

ARGUMENTS

- | | |
|--------------------|--|
| <i>class</i> | Specifies the resource class of the error message. |
| <i>default</i> | Specifies the default message to use. |
| <i>name</i> | Specifies the general kind of error. |
| <i>type</i> | Specifies the detailed name of the error. |
| <i>msg_handler</i> | Specifies the new fatal error procedure, which should not return or the nonfatal error procedure, which usually returns. |
| <i>num_params</i> | Specifies the number of values in the parameter list. |
| <i>params</i> | Specifies a pointer to a list of values to be stored in the message. |

DESCRIPTION

The **XtErrorMsg** function has been superseded by **XtAppErrorMsg**.

The **XtSetErrorMsgHandler** function has been superseded by **XtAppSetErrorMsgHandler**.

The **XtSetWarningMsgHandler** function has been superseded by **XtAppSetWarningMsgHandler**.

The **XtWarningMsg** function has been superseded by **XtAppWarningMsg**

SEE ALSO

XtAppErrorMsg(3)

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface