

NAME

acl_clear_perms - clear permissions from a permission set

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <sys/types.h>
#include <sys/acl.h>
```

```
int
acl_clear_perms(acl_permset_t permset_d);
```

DESCRIPTION

The **acl_clear_perms()** function is a POSIX.1e call that clears all permissions from permissions set *permset_d*.

RETURN VALUES

The **acl_clear_perms()** function returns the value 0 if successful; otherwise the value -1 is returned and the global variable *errno* is set to indicate the error.

ERRORS

The **acl_clear_perms()** function fails if:

[EINVAL] Argument *permset_d* is not a valid descriptor for a permission set.

SEE ALSO

[acl\(3\)](#), [acl_add_perm\(3\)](#), [acl_delete_perm\(3\)](#), [acl_get_permset\(3\)](#), [acl_set_permset\(3\)](#), [posix1e\(3\)](#)

STANDARDS

POSIX.1e is described in IEEE POSIX.1e draft 17.

HISTORY

POSIX.1e support was introduced in FreeBSD 4.0. The **acl_clear_perms()** function was added in FreeBSD 5.0.

AUTHORS

The **acl_clear_perms()** function was written by Chris D. Faulhaber <jedgar@fxp.org>.