

NAME

acl_set_permset - set the permissions of an ACL entry

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <sys/types.h>
```

```
#include <sys/acl.h>
```

int

```
acl_set_permset(acl_entry_t entry_d, acl_permset_t permset_d);
```

DESCRIPTION

The **acl_set_permset()** function is a POSIX.1e call that sets the permissions of ACL entry *entry_d* with the permissions contained in *permset_d*.

RETURN VALUES

The **acl_set_permset()** function returns the value 0 if successful; otherwise the value -1 is returned and the global variable *errno* is set to indicate the error.

ERRORS

The **acl_set_permset()** function fails if:

[EINVAL] Argument *entry_d* is not a valid descriptor for an ACL entry.

SEE ALSO

acl(3), acl_add_perm(3), acl_clear_perms(3), acl_delete_perm(3), acl_get_permset(3), posix1e(3)

STANDARDS

POSIX.1e is described in IEEE POSIX.1e draft 17.

HISTORY

POSIX.1e support was introduced in FreeBSD 4.0. The **acl_set_permset()** function was added in FreeBSD 5.0.

AUTHORS

The **acl_set_permset()** function was written by Chris D. Faulhaber <jedgar@fxp.org>.