NAME

aout - kernel support for executing binary files in legacy a.out format

SYNOPSIS

kldload a.out

DESCRIPTION

The a.out(5) executable format was used before the release of FreeBSD 3.0. Since i386 was the only supported architecture at that time, a.out(5) executables can only be activated on platforms that support execution of i386 code, such as i386 and amd64.

To add kernel support for old syscalls and old syscall invocation methods, place the following options in the kernel configuration file:

options COMPAT_43 options COMPAT_FREEBSD32

The COMPAT_FREEBSD32 option is only required on 64-bit CPU architectures.

The *aout.ko* module needs to be loaded with the kldload(8) utility in order to support the a.out(5) image activator:

kldload aout

Alternatively, to load the module at boot time, place the following line in loader.conf(5):

aout_load="YES"

The a.out(5) format was mainstream quite a long time ago. Reasonable default settings and security requirements of modern operating systems today contradict the default environment of that time and require adjustments of the system to mimic natural environment for old binaries.

The following sysctl(8) tunables are useful for this:

security.bsd.map_at_zero	Set to 1 to allow mapping of process pages at address 0. Some very old <i>ZMAGIC</i> executable images require text mapping at address 0.
kern.pid_max	Old versions of FreeBSD used signed 16-bit type for <i>pid_t</i> . Current kernels use 32-bit type for <i>pid_t</i>

	and allow process id's up to 99999. Such values cannot be represented by old <i>pid_t</i> , mostly causing issues for processes using wait(2) syscalls, for example shells. Set the sysctl to 30000 to work around the problem.
kern.elf32.read_exec	Set to 1 to force any accessible memory mapping performed by 32-bit process to allow execution, see mmap(2). Old i386 CPUs did not have a bit in PTE which disallowed execution from the page, so many old programs did not specify <i>PROT_EXEC</i> even for mapping of executable code. The sysctl forces <i>PROT_EXEC</i> if mapping has any access allowed at all. The setting is only needed if the host architecture allows non-executable mappings.

SEE ALSO

execve(2), a.out(5), elf(5), sysctl(8)

HISTORY

The a.out(5) executable format was used on ancient AT&T UNIX and served as the main executable format for FreeBSD from the beginning up to FreeBSD 2.2.9. In FreeBSD 3.0 it was superseded by elf(5).

AUTHORS

The **aout** manual page was written by Konstantin Belousov <kib@FreeBSD.org>.

BUGS

On 64bit architectures, not all wrappers for older syscalls are implemented.