

NAME

appres - list X application resource database

SYNOPSIS

appres [class [instance]] [-1] [-V] [toolkitoptions]

DESCRIPTION

The *appres* program prints the resources seen by an application (or subhierarchy of an application) with the specified *class* and *instance* names. It can be used to determine which resources a particular program will load. For example,

```
% appres XTerm
```

will list the resources that any *xterm* program will load. If no application class is specified, the class *-AppResTest-* is used.

To match a particular instance name, specify an instance name explicitly after the class name, or use the normal Xt toolkit option. For example,

```
% appres XTerm myxterm
```

or

```
% appres XTerm -name myxterm
```

To list resources that match a subhierarchy of an application, specify hierarchical class and instance names. The number of class and instance components must be equal, and the instance name should not be specified with a toolkit option. For example,

```
% appres Xman.TopLevelShell.Form xman.topBox.form
```

will list the resources of widgets of *xman* *topBox* hierarchy. To list just the resources matching a specific level in the hierarchy, use the *-1* option. For example,

```
% appres XTerm.VT100 xterm.vt100 -1
```

will list the resources matching the *xterm* *vt100* widget.

The *-V* option prints the *appres* command version and exits.

SEE ALSO

X(7), *xrdb*(1), *listres*(1)

AUTHOR

Jim Fulton, MIT X Consortium