

NAME

asn1_expand_octet_string - API function

SYNOPSIS

```
#include <libtasn1.h>
```

```
int asn1_expand_octet_string(asn1_node_const definitions, asn1_node * element, const char *  
octetName, const char * objectName);
```

ARGUMENTS

asn1_node_const definitions

ASN1 definitions

asn1_node * element

pointer to an ASN1 structure

const char * octetName

name of the OCTET STRING field to expand.

const char * objectName

name of the OBJECT IDENTIFIER field to use to define the type for expansion.

DESCRIPTION

Expands an "OCTET STRING" element of a structure created from a DER decoding process (the **asn1_der_decoding()** function). The type used for expansion is the first one following the definition of the actual value of the OBJECT IDENTIFIER indicated by OBJECTNAME.

RETURNS

ASN1_SUCCESS if substitution OK, **ASN1_ELEMENT_NOT_FOUND** if *objectName* or *octetName* are not correct, **ASN1_VALUE_NOT_VALID** if it wasn't possible to find the type to use for expansion, or other errors depending on DER decoding.

COPYRIGHT

Copyright (C) 2006-2022 Free Software Foundation, Inc..

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libtasn1** is maintained as a Texinfo manual. If the **info** and **libtasn1** programs are properly installed at your site, the command

info libtasn1

should give you access to the complete manual. As an alternative you may obtain the manual from:

<https://www.gnu.org/software/libtasn1/manual/>