

**NAME**

**check\_utility\_compat** - determine whether a utility should be compatible

**LIBRARY**

Standard C Library (libc, -lc)

**SYNOPSIS**

```
#include <unistd.h>
```

*int*

```
check_utility_compat(const char *utility);
```

**DESCRIPTION**

The **check\_utility\_compat**() function checks whether *utility* should behave in a traditional (FreeBSD 4.7-compatible) manner, or in accordance with IEEE Std 1003.1-2001 ("POSIX.1"). The configuration is given as a comma-separated list of utility names; if the list is present but empty, all supported utilities assume their most compatible mode. The **check\_utility\_compat**() function first checks for an environment variable named `_COMPAT_FreeBSD_4`. If that environment variable does not exist, then **check\_utility\_compat**() will attempt to read the contents of a symbolic link named `/etc/compat-FreeBSD-4-util`. If no configuration is found, compatibility mode is disabled.

**RETURN VALUES**

The **check\_utility\_compat**() function returns zero if *utility* should implement strict IEEE Std 1003.1-2001 ("POSIX.1") behavior, and nonzero otherwise.

**FILES**

`/etc/compat-FreeBSD-4-util` If present, a symbolic link whose expansion gives system-wide default settings for the **check\_utility\_compat**() function.

**ERRORS**

No errors are detected.

**HISTORY**

The **check\_utility\_compat**() function first appeared in FreeBSD 5.0.

**AUTHORS**

This manual page was written by Garrett Wollman <wollman@FreeBSD.org>.