

NAME

erase, werase, clear, wclear, clrtobot, wclrtobot, clrtoeol, wclrtoeol - clear all or part of a *curses* window

SYNOPSIS

```
#include <curses.h>
```

```
int erase(void);
```

```
int werase(WINDOW *win);
```

```
int clear(void);
```

```
int wclear(WINDOW *win);
```

```
int clrtobot(void);
```

```
int wclrtobot(WINDOW *win);
```

```
int clrtoeol(void);
```

```
int wclrtoeol(WINDOW *win);
```

DESCRIPTION**erase, werase**

The **erase** and **werase** routines copy blanks to every position in the window, clearing the screen.

Blanks created by erasure have the current background rendition (as set by **wbkgdset(3X)**) merged into them.

clear, wclear

The **clear** and **wclear** routines are like **erase** and **werase**, but they also call **clearok(3X)**, so that the screen is cleared completely on the next call to **wrefresh** for that window and repainted from scratch.

clrtobot, wclrtobot

The **clrtobot** and **wclrtobot** routines erase from the cursor to the end of screen. That is, they erase all lines below the cursor in the window. Also, the current line to the right of the cursor, inclusive, is erased.

clrtoeol, wclrtoeol

The **clrtoeol** and **wclrtoeol** routines erase the current line to the right of the cursor, inclusive, to the end of the current line.

RETURN VALUE

All routines return the integer **OK** on success and **ERR** on failure.

X/Open defines no error conditions. In this implementation,

- ⊕ functions using a window pointer parameter return an error if it is null
- ⊕ **wclrtoeol** returns an error if the cursor position is about to wrap.

NOTES

Note that **erase**, **werase**, **clear**, **wclear**, **clrtoeol**, and **clrtoeol** may be macros.

PORTABILITY

These functions are described in X/Open Curses, Issue 4.

The SVr4.0 manual says that these functions could return "or a non-negative integer if **immedok** is set", referring to the return-value of **wrefresh**. In that implementation, **wrefresh** would return a count of the number of characters written to the terminal.

Some historic curses implementations had, as an undocumented feature, the ability to do the equivalent of **clearok(..., 1)** by saying **touchwin(stdscr)** or **clear(stdscr)**. This will not work under *ncurses*.

This implementation, and others such as Solaris, sets the current position to 0,0 after erasing via **werase** and **wclear**. That fact is not documented in other implementations, and may not be true of implementations which were not derived from SVr4 source.

Not obvious from the description, most implementations clear the screen after **wclear** even for a subwindow or derived window. If you do not want to clear the screen during the next **wrefresh**, use **werase** instead.

SEE ALSO

curses(3X), **curs_outopts(3X)**, **curs_refresh(3X)**, **curs_variables(3X)**