

NAME

cluster - find clusters in a graph and augment the graph with this information.

SYNOPSIS

```
cluster [-v?] [ -Ck ] [ -ck ] [ -o outfile ] [ files ]
```

DESCRIPTION

cluster takes as input a graph in DOT format, finds node clusters and augments the graph with this information. The clusters are specified by the "cluster" attribute attached to nodes; cluster values are non-negative integers. **cluster** attempts to maximize the modularity of the clustering. If the edge attribute "weight" is defined, this will be used in computing the clustering.

OPTIONS

The following options are supported:

-Ck specifies a targeted number of clusters that should be generated. The specified number *k* is only a suggestion and may not be realisable. If *k* == 0, the default, the number of clusters that approximately optimizes the modularity is returned.

-ck specifies clustering method. If *k* == 0, the default, modularity clustering will be used. If *k* == 1 modularity quality will be used.

-o*outfile*

Specifies that output should go into the file *outfile*. By default, *stdout* is used.

-v Verbose mode.

-? Prints the usage and exits.

EXAMPLES

Applying **cluster** to the following graph,

```
graph {  
  1--2 [weight=10.]  
  2--3 [weight=1]  
  3--4 [weight=10.]  
  4--5 [weight=10]  
  5--6 [weight=10]  
  3--6 [weight=0.1]  
  4--6 [weight=10.]
```

```
}
```

gives

```
graph {
  node [cluster="-1"];
  1 [cluster=1];
  2 [cluster=1];
  3 [cluster=2];
  4 [cluster=2];
  5 [cluster=2];
  6 [cluster=2];
  1 -- 2 [weight="10."];
  2 -- 3 [weight=1];
  3 -- 4 [weight="10."];
  4 -- 5 [weight=10];
  5 -- 6 [weight=10];
  3 -- 6 [weight="0.1"];
  4 -- 6 [weight="10."];
}
```

AUTHOR

Yifan Hu <yifanhu@yahoo.com>

SEE ALSO

gvmap(1)

Blondel, V.D., Guillaume, J.L., Lambiotte, R., Lefebvre, E.: Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment* (2008), P10008.