

NAME

devfs - device file system

SYNOPSIS

devfs /dev devfs rw 0 0

DESCRIPTION

The device file system, or **devfs**, provides access to kernel's device namespace in the global file system namespace. The conventional mount point is */dev*.

The file system includes several directories, links, symbolic links and devices, some of which can also be written. In a chroot'ed environment, devfs(8) can be used to create a new */dev* mount point.

The mknod(8) tool can be used to recover deleted device entries under **devfs**.

The fdscfs(5) filesystem is an alternate means for populating */dev/fd*. The character devices that both **devfs** and fdscfs(5) present in */dev/fd* correspond to the open file descriptors of the process accessing the directory. **devfs** only creates files for the standard file descriptors 0, 1 and 2. fdscfs(5) creates files for all open descriptors.

The options are as follows:

-o options

Use the specified mount *options*, as described in mount(8). The following devfs file system-specific options are available:

ruleset=ruleset

Set ruleset number *ruleset* as the current ruleset for the mount-point and apply all its rules. If the ruleset number *ruleset* does not exist, an empty ruleset with the number *ruleset* is created. See devfs(8) for more information on working with devfs rulesets.

FILES

/dev The normal **devfs** mount point.

EXAMPLES

To mount a **devfs** volume located on */mychroot/dev*:

```
mount -t devfs devfs /mychroot/dev
```

SEE ALSO

fdescfs(5), devfs(8), mount(8), make_dev(9)

HISTORY

The **devfs** file system first appeared in FreeBSD 2.0. It became the preferred method for accessing devices in FreeBSD 5.0 and the only method in FreeBSD 6.0. The **devfs** manual page first appeared in FreeBSD 2.2.

AUTHORS

The **devfs** manual page was written by Mike Pritchard <*mpp@FreeBSD.org*>.