

NAME

elf_getphnum - return the number of program headers in an ELF file

LIBRARY

ELF Access Library (libelf, -lelf)

SYNOPSIS

```
#include <libelf.h>
```

```
int  
elf_getphnum(Elf *elf, size_t *phnum);
```

DESCRIPTION

This function is deprecated. Please use function `elf_getphdrnum(3)` instead.

Function **elf_getphnum()** retrieves the number of ELF program headers associated with descriptor *elf* and stores it into the location pointed to by argument *phnum*.

This routine allows applications to uniformly process both normal ELF objects and ELF objects that use extended numbering.

RETURN VALUES

Function **elf_getphnum()** returns a non-zero value if successful, or zero in case of an error.

ERRORS

Function **elf_getphnum()** can fail with the following errors:

[ELF_E_ARGUMENT]

A NULL value was passed in for argument *elf*.

[ELF_E_ARGUMENT]

Argument *elf* was not for an ELF file.

[ELF_E_ARGUMENT]

Argument *elf* lacks an ELF Executable Header.

[ELF_E_HEADER] The ELF Executable Header associated with argument *elf* was corrupt.

[ELF_E_SECTION] The section header at index SHN_UNDEF was corrupt.

SEE ALSO

`elf(3)`, `elf32_getehdr(3)`, `elf64_getehdr(3)`, `elf_getident(3)`, `elf_getphdrnum(3)`, `elf_getshdrnum(3)`,
`elf_getshdrstrndx(3)`, `gelf(3)`, `gelf_getehdr(3)`