NAME

fhopen, fhstat, fhstatfs - access file via file handle

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

#include <sys/param.h>
#include <sys/mount.h>
#include <sys/stat.h>

int
fhopen(const fhandle_t *fhp, int flags);

int

fhstat(const fhandle_t *fhp, struct stat *sb);

int
fhstatfs(const fhandle_t *fhp, struct statfs *buf);

DESCRIPTION

These system calls provide a means to access a file given the file handle *fhp*. As this method bypasses directory access restrictions, these calls are restricted to the superuser.

The **fhopen**() system call opens the file referenced by *fhp* for reading and/or writing as specified by the argument *flags* and returns the file descriptor to the calling process. The *flags* argument is specified by *or*'ing together the flags used for the open(2) system call. All said flags are valid except for O_CREAT.

The **fhstat**() and **fhstatfs**() system calls provide the functionality of the fstat(2) and fstatfs(2) calls except that they return information for the file referred to by *fhp* rather than an open file.

RETURN VALUES

Upon successful completion, **fhopen**() returns the file descriptor for the opened file; otherwise the value -1 is returned and the global variable *errno* is set to indicate the error.

The **fhstat**() and **fhstatfs**() functions return the value 0 if successful; otherwise the value -1 is returned and the global variable *errno* is set to indicate the error.

ERRORS

In addition to the errors returned by open(2), fstat(2), and fstatfs(2) respectively, fhopen(), fhstat(), and

fhstatfs() will return

[EINVAL]	Calling fhopen () with O_	CREAT set.

[ESTALE] The file handle *fhp* is no longer valid.

SEE ALSO

fstat(2), fstatfs(2), getfh(2), open(2)

HISTORY

The **fhopen**(), **fhstat**(), and **fhstatfs**() system calls first appeared in NetBSD 1.5 and were adapted to FreeBSD 4.0 by Alfred Perlstein.

AUTHORS

This manual page was written by William Studenmund for NetBSD.