

NAME

fido_cred_new, **fido_cred_free**, **fido_cred_pin_minlen**, **fido_cred_prot**, **fido_cred_fmt**, **fido_cred_rp_id**,
fido_cred_rp_name, **fido_cred_user_name**, **fido_cred_display_name**, **fido_cred_authdata_ptr**,
fido_cred_authdata_raw_ptr, **fido_cred_clientdata_hash_ptr**, **fido_cred_id_ptr**, **fido_cred_aaguid_ptr**,
fido_cred_largeblob_key_ptr, **fido_cred_pubkey_ptr**, **fido_cred_sig_ptr**, **fido_cred_user_id_ptr**,
fido_cred_x5c_ptr, **fido_cred_attstmt_ptr**, **fido_cred_authdata_len**, **fido_cred_authdata_raw_len**,
fido_cred_clientdata_hash_len, **fido_cred_id_len**, **fido_cred_aaguid_len**, **fido_cred_largeblob_key_len**,
fido_cred_pubkey_len, **fido_cred_sig_len**, **fido_cred_user_id_len**, **fido_cred_x5c_len**,
fido_cred_attstmt_len, **fido_cred_type**, **fido_cred_flags**, **fido_cred_sigcount** - FIDO2 credential API

SYNOPSIS

```
#include <fido.h>
```

fido_cred_t *

fido_cred_new(*void*);

void

fido_cred_free(*fido_cred_t* ***cred_p*);

size_t

fido_cred_pin_minlen(*const fido_cred_t* **cred*);

int

fido_cred_prot(*const fido_cred_t* **cred*);

const char *

fido_cred_fmt(*const fido_cred_t* **cred*);

const char *

fido_cred_rp_id(*const fido_cred_t* **cred*);

const char *

fido_cred_rp_name(*const fido_cred_t* **cred*);

const char *

fido_cred_user_name(*const fido_cred_t* **cred*);

const char *

fido_cred_display_name(*const fido_cred_t* **cred*);

```
const unsigned char *
fido_cred_authdata_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_authdata_raw_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_clientdata_hash_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_id_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_aaguid_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_largeblob_key_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_pubkey_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_sig_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_user_id_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_x5c_ptr(const fido_cred_t *cred);

const unsigned char *
fido_cred_attstmt_ptr(const fido_cred_t *cred);

size_t
fido_cred_authdata_len(const fido_cred_t *cred);

size_t
fido_cred_authdata_raw_len(const fido_cred_t *cred);

size_t
```

fido_cred_clientdata_hash_len(*const fido_cred_t *cred*);

size_t

fido_cred_id_len(*const fido_cred_t *cred*);

size_t

fido_cred_aaguid_len(*const fido_cred_t *cred*);

size_t

fido_cred_largeblob_key_len(*const fido_cred_t *cred*);

size_t

fido_cred_pubkey_len(*const fido_cred_t *cred*);

size_t

fido_cred_sig_len(*const fido_cred_t *cred*);

size_t

fido_cred_user_id_len(*const fido_cred_t *cred*);

size_t

fido_cred_x5c_len(*const fido_cred_t *cred*);

size_t

fido_cred_attstmt_len(*const fido_cred_t *cred*);

int

fido_cred_type(*const fido_cred_t *cred*);

uint8_t

fido_cred_flags(*const fido_cred_t *cred*);

uint32_t

fido_cred_sigcount(*const fido_cred_t *cred*);

DESCRIPTION

FIDO2 credentials are abstracted in *libfido2* by the *fido_cred_t* type. The functions described in this page allow a *fido_cred_t* type to be allocated, deallocated, and inspected. For other operations on *fido_cred_t*, please refer to *fido_cred_set_authdata*(3), *fido_cred_exclude*(3), *fido_cred_verify*(3), and *fido_dev_make_cred*(3).

The **fido_cred_new()** function returns a pointer to a newly allocated, empty *fido_cred_t* type. If memory cannot be allocated, NULL is returned.

The **fido_cred_free()** function releases the memory backing **cred_p*, where **cred_p* must have been previously allocated by **fido_cred_new()**. On return, **cred_p* is set to NULL. Either *cred_p* or **cred_p* may be NULL, in which case **fido_cred_free()** is a NOP.

If the CTAP 2.1 FIDO_EXT_MINPINLEN extension is enabled on *cred*, then the **fido_cred_pin_minlen()** function returns the minimum PIN length of *cred*. Otherwise, **fido_cred_pin_minlen()** returns zero. See *fido_cred_set_pin_minlen(3)* on how to enable this extension.

If the CTAP 2.1 FIDO_EXT_CRED_PROTECT extension is enabled on *cred*, then the **fido_cred_prot()** function returns the protection of *cred*. Otherwise, **fido_cred_prot()** returns zero. See *fido_cred_set_prot(3)* for the protection policies understood by *libfido2*.

The **fido_cred_fmt()** function returns a pointer to a NUL-terminated string containing the attestation statement format identifier of *cred*, or NULL if *cred* does not have a format set.

The **fido_cred_rp_id()**, **fido_cred_rp_name()**, **fido_cred_user_name()**, and **fido_cred_display_name()** functions return pointers to NUL-terminated strings holding the relying party ID, relying party name, user name, and user display name attributes of *cred*, or NULL if the respective entry is not set.

The **fido_cred_authdata_ptr()**, **fido_cred_authdata_raw_ptr()**, **fido_cred_clientdata_hash_ptr()**, **fido_cred_id_ptr()**, **fido_cred_aaguid_ptr()**, **fido_cred_largeblob_key_ptr()**, **fido_cred_pubkey_ptr()**, **fido_cred_sig_ptr()**, **fido_cred_user_id_ptr()**, **fido_cred_x5c_ptr()**, and **fido_cred_attstmt_ptr()** functions return pointers to the CBOR-encoded and raw authenticator data, client data hash, ID, authenticator attestation GUID, "largeBlobKey", public key, signature, user ID, x509 certificate, and attestation statement parts of *cred*, or NULL if the respective entry is not set.

The corresponding length can be obtained by **fido_cred_authdata_len()**, **fido_cred_authdata_raw_len()**, **fido_cred_clientdata_hash_len()**, **fido_cred_id_len()**, **fido_cred_aaguid_len()**, **fido_cred_largeblob_key_len()**, **fido_cred_pubkey_len()**, **fido_cred_sig_len()**, **fido_cred_user_id_len()**, **fido_cred_x5c_len()**, and **fido_cred_attstmt_len()**.

The authenticator data, x509 certificate, and signature parts of a credential are typically passed to a FIDO2 server for verification.

The **fido_cred_type()** function returns the COSE algorithm of *cred*.

The **fido_cred_flags()** function returns the authenticator data flags of *cred*.

The **fido_cred_sigcount()** function returns the authenticator data signature counter of *cred*.

RETURN VALUES

The authenticator data returned by **fido_cred_authdata_ptr()** is a CBOR-encoded byte string, as obtained from the authenticator. To obtain the decoded byte string, use **fido_cred_authdata_raw_ptr()**.

If not NULL, pointers returned by **fido_cred_fmt()**, **fido_cred_authdata_ptr()**,
fido_cred_clientdata_hash_ptr(), **fido_cred_id_ptr()**, **fido_cred_aaguid_ptr()**,
fido_cred_largeblob_key_ptr(), **fido_cred_pubkey_ptr()**, **fido_cred_sig_ptr()**, and **fido_cred_x5c_ptr()** are guaranteed to exist until any API function that takes *cred* without the *const* qualifier is invoked.

SEE ALSO

[fido_cred_exclude\(3\)](#), [fido_cred_set_authdata\(3\)](#), [fido_cred_set_pin_minlen\(3\)](#), [fido_cred_set_prot\(3\)](#),
[fido_cred_verify\(3\)](#), [fido_credman_metadata_new\(3\)](#), [fido_dev_largeblob_get\(3\)](#),
[fido_dev_make_cred\(3\)](#)