

**NAME**

**set\_field\_just**, **field\_just** - retrieve field characteristics

**SYNOPSIS**

```
#include <form.h>
```

```
int set_field_just(FIELD *field, int justification);  
int field_just(const FIELD *field);
```

**DESCRIPTION**

The function **set\_field\_just** sets the justification attribute of a field; **field\_just** returns a field's justification attribute. The attribute may be one of NO\_JUSTIFICATION, JUSTIFY\_RIGHT, JUSTIFY\_LEFT, or JUSTIFY\_CENTER.

**RETURN VALUE**

The function **field\_just** returns one of: NO\_JUSTIFICATION, JUSTIFY\_RIGHT, JUSTIFY\_LEFT, or JUSTIFY\_CENTER.

The function **set\_field\_just** returns one of the following:

**E\_OK**

The routine succeeded.

**E\_SYSTEM\_ERROR**

System error occurred (see **errno(3)**).

**E\_BAD\_ARGUMENT**

Routine detected an incorrect or out-of-range argument.

**SEE ALSO**

**curses(3X)** and related pages whose names begin "form\_" for detailed descriptions of the entry points.

**NOTES**

The header file **<form.h>** automatically includes the header file **<curses.h>**.

**PORTABILITY**

These routines emulate the System V forms library. They were not supported on Version 7 or BSD versions.

**AUTHORS**

form\_field\_just(3X)

form\_field\_just(3X)

Juergen Pfeifer. Manual pages and adaptation for new curses by Eric S. Raymond.

form\_field\_just(3X)