

NAME

set_field_just, **field_just** - retrieve field characteristics

SYNOPSIS

```
#include <form.h>
```

```
int set_field_just(FIELD *field, int justification);  
int field_just(const FIELD *field);
```

DESCRIPTION

The function **set_field_just** sets the justification attribute of a field; **field_just** returns a field's justification attribute. The attribute may be one of NO_JUSTIFICATION, JUSTIFY_RIGHT, JUSTIFY_LEFT, or JUSTIFY_CENTER.

RETURN VALUE

The function **field_just** returns one of: NO_JUSTIFICATION, JUSTIFY_RIGHT, JUSTIFY_LEFT, or JUSTIFY_CENTER.

The function **set_field_just** returns one of the following:

E_OK

The routine succeeded.

E_SYSTEM_ERROR

System error occurred (see **errno(3)**).

E_BAD_ARGUMENT

Routine detected an incorrect or out-of-range argument.

SEE ALSO

curses(3X) and related pages whose names begin "form_" for detailed descriptions of the entry points.

NOTES

The header file **<form.h>** automatically includes the header file **<curses.h>**.

PORTABILITY

These routines emulate the System V forms library. They were not supported on Version 7 or BSD versions.

AUTHORS

form_field_just(3X)

form_field_just(3X)

Juergen Pfeifer. Manual pages and adaptation for new curses by Eric S. Raymond.

form_field_just(3X)