

NAME

fribidi_set_debug - set debug state

SYNOPSIS

```
#include <fribidi.h>
```

```
int fribidi_set_debug(int state);
```

PARAMETERS

int state

New state to set.

DESCRIPTION

Set debug state.

SEE ALSO

fribidi_shape_arabic(3), fribidi_get_par_direction(3), fribidi_get_par_embedding_levels_ex(3), fribidi_reorder_line(3), fribidi_get_bidi_type(3), fribidi_get_bidi_types(3), fribidi_get_bidi_type_name(3), fribidi_debug_status(3), fribidi_charset_to_unicode(3), fribidi_unicode_to_charset(3), fribidi_parse_charset(3), fribidi_mirroring_status(3), fribidi_set_mirroring(3), fribidi_reorder_nsm_status(3), fribidi_set_reorder_nsm(3), fribidi_log2vis_get_embedding_levels(3), fribidi_get_type(3), fribidi_get_type_internal(3), fribidi_get_par_embedding_levels(3), fribidi_join_arabic(3), fribidi_get_joining_type(3), fribidi_get_joining_types(3), fribidi_get_joining_type_name(3), fribidi_get_mirror_char(3), fribidi_shape_mirroring(3), fribidi_get_bracket(3), fribidi_get_bracket_types(3), fribidi_shape(3), fribidi_remove_bidi_marks(3), fribidi_log2vis(3)