

**NAME**

**g\_new\_consumer**, **g\_destroy\_consumer** - GEOM consumers management

**SYNOPSIS**

```
#include <geom/geom.h>
```

```
struct g_consumer *
```

```
g_new_consumer(struct g_geom *gp);
```

```
void
```

```
g_destroy_consumer(struct g_consumer *cp);
```

**DESCRIPTION**

A GEOM consumer is the backdoor through which a geom connects to another GEOM provider and through which I/O requests are sent.

The **g\_new\_consumer**() function creates a new consumer on geom *gp*. Before using the new consumer, it has to be attached to a provider with **g\_attach**(9) and opened with **g\_access**(9).

The **g\_destroy\_consumer**() function destroys the given consumer and cancels all related pending events. This function is the last stage of killing an unwanted consumer.

**RESTRICTIONS/CONDITIONS**

**g\_new\_consumer**():

The geom *gp* has to have an *orphan* method defined.

The topology lock has to be held.

**g\_destroy\_consumer**():

The consumer must not be attached to a provider.

The access count has to be 0.

The topology lock has to be held.

**RETURN VALUES**

The **g\_new\_consumer**() function returns a pointer to the newly created consumer.

**EXAMPLES**

Create consumer, attach it to given provider, gain read access and clean up.

```
void
some_function(struct g_geom *mygeom, struct g_provider *pp)
{
    struct g_consumer *cp;

    g_topology_assert();

    /* Create new consumer on 'mygeom' geom. */
    cp = g_new_consumer(mygeom);
    /* Attach newly created consumer to given provider. */
    if (g_attach(cp, pp) != 0) {
        g_destroy_consumer(cp);
        return;
    }
    /* Open provider for reading through our consumer. */
    if (g_access(cp, 1, 0, 0) != 0) {
        g_detach(cp);
        g_destroy_consumer(cp);
        return;
    }

    g_topology_unlock();
    /*
     * Read data from provider.
     */
    g_topology_lock();

    /* Disconnect from provider (release access count). */
    g_access(cp, -1, 0, 0);
    /* Detach from provider. */
    g_detach(cp);
    /* Destroy consumer. */
    g_destroy_consumer(cp);
}
```

**SEE ALSO**

geom(4), DECLARE\_GEOM\_CLASS(9), g\_access(9), g\_attach(9), g\_bio(9), g\_data(9), g\_event(9),

[g\\_geom\(9\)](#), [g\\_provider\(9\)](#), [g\\_provider\\_by\\_name\(9\)](#), [g\\_wither\\_geom\(9\)](#)

## **AUTHORS**

This manual page was written by Pawel Jakub Dawidek <[pjd@FreeBSD.org](mailto:pjd@FreeBSD.org)>.