

NAME

gdk-pixbuf-query-loaders - GdkPixbuf loader registration utility

SYNOPSIS

gdk-pixbuf-query-loaders [OPTIONS...] [MODULES..]

DESCRIPTION

gdk-pixbuf-query-loaders collects information about loadable modules for **gdk-pixbuf** and writes it to the default cache file location, or to **stdout**.

If called without arguments, it looks for modules in the **gdk-pixbuf** loader directory.

If called with arguments, it looks for the specified modules. The arguments may be absolute or relative paths.

Normally, the output of **gdk-pixbuf-query-loaders** is written to **\$libdir/gdk-pixbuf-2.0/2.10.0/loaders.cache**, where **gdk-pixbuf** looks for it by default. If it is written to some other location, the environment variable **GDK_PIXBUF_MODULE_FILE** can be set to point **gdk-pixbuf** at the file.

OPTIONS**--update-cache**

Writes the output to the default cache location instead of the standard output.

ENVIRONMENT

The environment variable **GDK_PIXBUF_MODULEDIR** can be used to specify a different loader directory.

The default **gdk-pixbuf** loader directory is **LIBDIR/gdk-pixbuf-2.0/VERSION/loaders**, where:

- ⊕ **LIBDIR** is the libdir used when building **gdk-pixbuf**
- ⊕ **VERSION** is the ABI version for **gdk-pixbuf** loaders