

NAME

gendict - Compiles word list into ICU string trie dictionary

SYNOPSIS

gendict [**--uchars** | **--bytes** **--transform** *transform*] [**-h**, **-?**, **--help**] [**-V**, **--version**] [**-c**, **--copyright**] [**-v**, **--verbose**] [**-i**, **--icudatadir** *directory*] *input-file* *output-file*

DESCRIPTION

gendict reads the word list from *dictionary-file* and creates a string trie dictionary file. Normally this data file has the **.dict** extension.

Words begin at the beginning of a line and are terminated by the first whitespace. Lines that begin with whitespace are ignored.

OPTIONS**-h, -?, --help**

Print help about usage and exit.

-V, --version

Print the version of **gendict** and exit.

-c, --copyright

Embeds the standard ICU copyright into the *output-file*.

-v, --verbose

Display extra informative messages during execution.

-i, --icudatadir *directory*

Look for any necessary ICU data files in *directory*. For example, the file **pnames.icu** must be located when ICU's data is not built as a shared library. The default ICU data directory is specified by the environment variable **ICU_DATA**. Most configurations of ICU do not require this argument.

--uchars

Set the output trie type to UChar. Mutually exclusive with **--bytes**.

--bytes

Set the output trie type to Bytes. Mutually exclusive with **--uchars**.

--transform

Set the transform type. Should only be specified with **--bytes**. Currently supported transforms are: **offset-<hex-number>**, which specifies an offset to subtract from all input characters. It should be noted that the offset transform also maps U+200D to 0xFF and U+200C to 0xFE, in order to offer compatibility to languages that require these characters. A transform must be specified for a bytes trie, and when applied to the non-value characters in the *input-file* must produce output between 0x00 and 0xFF.

input-file

The source file to read.

output-file

The file to write the output dictionary to.

CAVEATS

The *input-file* is assumed to be encoded in UTF-8. The integers in the *input-file* that are used as values must be made up of ASCII digits. They may be specified either in hex, by using a 0x prefix, or in decimal. Either **--bytes** or **--uchars** must be specified.

ENVIRONMENT**ICU_DATA**

Specifies the directory containing ICU data. Defaults to **/\${prefix}/share/icu/73.2/**. Some tools in ICU depend on the presence of the trailing slash. It is thus important to make sure that it is present if **ICU_DATA** is set.

AUTHORS

Maxime Serrano

VERSION

1.0

COPYRIGHT

Copyright (C) 2012 International Business Machines Corporation and others

SEE ALSO

<http://www.icu-project.org/userguide/boundaryAnalysis.html>