

NAME

getarginit() - initialize properties for getargs() type functions

SYNOPSIS

```
#include <schily/getargs.h>
```

```
int getarginit(propg, flags)
```

```
    struct ga_props *props; /* control properties */
```

```
    int flags;             /* to control option parsing behavior */
```

DESCRIPTION

getarginit() initializes **struct ga_props** as needed by the functions **getlargs()**, **getlallargs()**, **getlfiles()**, **getvargs()**, **getvallargs()**, **getvfiles()**.

The *flags* argument controls the behavior of the named functions. If the value is **0**, the default behavior as documented in the man pages is used. The following flags are possible and may be combined:

GAF_DEFAULT Use the default behavior.

GAF_NO_PLUS Options may not start with a “+” even if they are marked with a + in the format string.

GAF_NO_EQUAL Disallow “=” between option name and value.

GAF_NEED_DASH A dash is needed before an option that takes an argument. Options in the form *name=value* are not allowed.

GAF_DELIM_DASHDASH

The special argument “--” stops option parsing even when using **getallargs()**, **getlallargs()**, **getvallargs()**.

GAF_SINGLEARG In a string with combined single character options, the last option character may be an option that has an argument.

GAF_POSIX

This macro enforces **POSIX** behavior and expands to **GAF_NO_PLUS | GAF_NO_EQUAL | GAF_SINGLEARG**. This value may not be combined with other flags.

RETURNS

- 0** No error occurred.

- 1** The version of the library was too old for the calling program.

SEE ALSO

getlargs(3), getlallargs(3), getlfiles(3), getvargs(3), getvallargs(3), getvfiles(3).

BUGS

None currently known.

Mail bugs and suggestions to **schilytools@mlists.in-berlin.de** or open a ticket at **<https://codeberg.org/schilytools/schilytools/issues>**.

The mailing list archive may be found at:

<https://mlists.in-berlin.de/mailman/listinfo/schilytools-mlists.in-berlin.de>.

AUTHOR

Joerg Schilling and the schilytools project authors.