

NAME

getipnodebyname, **getipnodebyaddr**, **freehostent** - nodename-to-address and address-to-nodename translation

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <sys/types.h>
```

```
#include <sys/socket.h>
```

```
#include <netdb.h>
```

```
struct hostent *
```

```
getipnodebyname(const char *name, int af, int flags, int *error_num);
```

```
struct hostent *
```

```
getipnodebyaddr(const void *src, size_t len, int af, int *error_num);
```

```
void
```

```
freehostent(struct hostent *ptr);
```

DESCRIPTION

The **getipnodebyname**() and **getipnodebyaddr**() functions are very similar to **gethostbyname**(3), **gethostbyname2**(3) and **gethostbyaddr**(3). The functions cover all the functionalities provided by the older ones, and provide better interface to programmers. The functions require additional arguments, *af*, and *flags*, for specifying address family and operation mode. The additional arguments allow programmer to get address for a nodename, for specific address family (such as AF_INET or AF_INET6). The functions also require an additional pointer argument, *error_num* to return the appropriate error code, to support thread safe error code returns.

The type and usage of the return value, struct hostent is described in **gethostbyname**(3).

For **getipnodebyname**(), the *name* argument can be either a node name or a numeric address string (i.e., a dotted-decimal IPv4 address or an IPv6 hex address). The *af* argument specifies the address family, either AF_INET or AF_INET6. The *flags* argument specifies the types of addresses that are searched for, and the types of addresses that are returned. We note that a special flags value of AI_DEFAULT (defined below) should handle most applications. That is, porting simple applications to use IPv6 replaces the call

```
hptr = gethostbyname(name);
```

with

```
hptr = getipnodebyname(name, AF_INET6, AI_DEFAULT, &error_num);
```

Applications desiring finer control over the types of addresses searched for and returned, can specify other combinations of the *flags* argument.

A *flags* of 0 implies a strict interpretation of the *af* argument:

- If *flags* is 0 and *af* is AF_INET, then the caller wants only IPv4 addresses. A query is made for A records. If successful, the IPv4 addresses are returned and the *h_length* member of the *hostent* structure will be 4, else the function returns a NULL pointer.
- If *flags* is 0 and if *af* is AF_INET6, then the caller wants only IPv6 addresses. A query is made for AAAA records. If successful, the IPv6 addresses are returned and the *h_length* member of the *hostent* structure will be 16, else the function returns a NULL pointer.

Other constants can be logically-ORed into the *flags* argument, to modify the behavior of the function.

- If the AI_V4MAPPED flag is specified along with an *af* of AF_INET6, then the caller will accept IPv4-mapped IPv6 addresses. That is, if no AAAA records are found then a query is made for A records and any found are returned as IPv4-mapped IPv6 addresses (*h_length* will be 16). The AI_V4MAPPED flag is ignored unless *af* equals AF_INET6.
- The AI_V4MAPPED_CFG flag is exact same as the AI_V4MAPPED flag only if the kernel supports IPv4-mapped IPv6 address.
- If the AI_ALL flag is used in conjunction with the AI_V4MAPPED flag, and only used with the IPv6 address family. When AI_ALL is logically or'd with AI_V4MAPPED flag then the caller wants all addresses: IPv6 and IPv4-mapped IPv6. A query is first made for AAAA records and if successful, the IPv6 addresses are returned. Another query is then made for A records and any found are returned as IPv4-mapped IPv6 addresses. *h_length* will be 16. Only if both queries fail does the function return a NULL pointer. This flag is ignored unless *af* equals AF_INET6. If both AI_ALL and AI_V4MAPPED are specified, AI_ALL takes precedence.
- The AI_ADDRCONFIG flag specifies that a query for AAAA records should occur only if the node has at least one IPv6 source address configured and a query for A records should occur only if the node has at least one IPv4 source address configured.

For example, if the node has no IPv6 source addresses configured, and *af* equals AF_INET6, and the

node name being looked up has both AAAA and A records, then: (a) if only AI_ADDRCONFIG is specified, the function returns a NULL pointer; (b) if AI_ADDRCONFIG | AI_V4MAPPED is specified, the A records are returned as IPv4-mapped IPv6 addresses;

The special flags value of AI_DEFAULT is defined as

```
#define AI_DEFAULT (AI_V4MAPPED_CFG | AI_ADDRCONFIG)
```

We noted that the **getipnodebyname()** function must allow the *name* argument to be either a node name or a literal address string (i.e., a dotted-decimal IPv4 address or an IPv6 hex address). This saves applications from having to call `inet_pton(3)` to handle literal address strings. When the *name* argument is a literal address string, the *flags* argument is always ignored.

There are four scenarios based on the type of literal address string and the value of the *af* argument. The two simple cases are when *name* is a dotted-decimal IPv4 address and *af* equals AF_INET, or when *name* is an IPv6 hex address and *af* equals AF_INET6. The members of the returned hostent structure are: *h_name* points to a copy of the *name* argument, *h_aliases* is a NULL pointer, *h_addrtype* is a copy of the *af* argument, *h_length* is either 4 (for AF_INET) or 16 (for AF_INET6), *h_addr_list[0]* is a pointer to the 4-byte or 16-byte binary address, and *h_addr_list[1]* is a NULL pointer.

When *name* is a dotted-decimal IPv4 address and *af* equals AF_INET6, and AI_V4MAPPED is specified, an IPv4-mapped IPv6 address is returned: *h_name* points to an IPv6 hex address containing the IPv4-mapped IPv6 address, *h_aliases* is a NULL pointer, *h_addrtype* is AF_INET6, *h_length* is 16, *h_addr_list[0]* is a pointer to the 16-byte binary address, and *h_addr_list[1]* is a NULL pointer.

It is an error when *name* is an IPv6 hex address and *af* equals AF_INET. The function's return value is a NULL pointer and the value pointed to by *error_num* equals HOST_NOT_FOUND.

The **getipnodebyaddr()** function takes almost the same argument as `gethostbyaddr(3)`, but adds a pointer to return an error number. Additionally it takes care of IPv4-mapped IPv6 addresses, and IPv4-compatible IPv6 addresses.

The **getipnodebyname()** and **getipnodebyaddr()** functions dynamically allocate the structure to be returned to the caller. The **freehostent()** function reclaims memory region allocated and returned by **getipnodebyname()** or **getipnodebyaddr()**.

FILES

/etc/hosts

/etc/nsswitch.conf

/etc/resolv.conf

DIAGNOSTICS

The **getipnodebyname()** and **getipnodebyaddr()** functions returns NULL on errors. The integer values pointed to by *error_num* may then be checked to see whether this is a temporary failure or an invalid or unknown host. The meanings of each error code are described in `gethostbyname(3)`.

SEE ALSO

`getaddrinfo(3)`, `gethostbyaddr(3)`, `gethostbyname(3)`, `getnameinfo(3)`, `hosts(5)`, `nsswitch.conf(5)`, `services(5)`, `hostname(7)`

R. Gilligan, S. Thomson, J. Bound, and W. Stevens, *Basic Socket Interface Extensions for IPv6*, RFC2553, March 1999.

STANDARDS

The **getipnodebyname()** and **getipnodebyaddr()** functions are documented in "Basic Socket Interface Extensions for IPv6" (RFC2553).

HISTORY

The implementation first appeared in KAME advanced networking kit.

BUGS

The **getipnodebyname()** and **getipnodebyaddr()** functions do not handle scoped IPv6 address properly. If you use these functions, your program will not be able to handle scoped IPv6 addresses. For IPv6 address manipulation, **getaddrinfo(3)** and **getnameinfo(3)** are recommended.

The text was shamelessly copied from RFC2553.