

NAME

gnutls_aead_cipher_init - API function

SYNOPSIS

```
#include <gnutls/crypto.h>
```

```
int gnutls_aead_cipher_init(gnutls_aead_cipher_hd_t * handle, gnutls_cipher_algorithm_t cipher, const gnutls_datum_t * key);
```

ARGUMENTS

gnutls_aead_cipher_hd_t * handle
is a **gnutls_aead_cipher_hd_t** type.

gnutls_cipher_algorithm_t cipher
the authenticated-encryption algorithm to use

const gnutls_datum_t * key
The key to be used for encryption

DESCRIPTION

This function will initialize an context that can be used for encryption/decryption of data. This will effectively use the current crypto backend in use by gnutls or the cryptographic accelerator in use.

RETURNS

Zero or a negative error code on error.

SINCE

3.4.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>. Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>