

**NAME**

gnutls\_alert\_get - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
gnutls_alert_description_t gnutls_alert_get(gnutls_session_t session);
```

**ARGUMENTS**

gnutls\_session\_t session

is a **gnutls\_session\_t** type.

**DESCRIPTION**

This function will return the last alert number received. This function should be called when **GNUTLS\_E\_WARNING\_ALERT\_RECEIVED** or **GNUTLS\_E\_FATAL\_ALERT\_RECEIVED** errors are returned by a gnutls function. The peer may send alerts if he encounters an error. If no alert has been received the returned value is undefined.

**RETURNS**

the last alert received, a **gnutls\_alert\_description\_t** value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>