

NAME

gnutls_anon_set_server_dh_params - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_anon_set_server_dh_params(gnutls_anon_server_credentials_t res, gnutls_dh_params_t dh_params);
```

ARGUMENTS

gnutls_anon_server_credentials_t res
is a gnutls_anon_server_credentials_t type

gnutls_dh_params_t dh_params
The Diffie-Hellman parameters.

DESCRIPTION

This function will set the Diffie-Hellman parameters for an anonymous server to use. These parameters will be used in Anonymous Diffie-Hellman cipher suites.

DEPRECATED

This function is unnecessary and discouraged on GnuTLS 3.6.0 or later. Since 3.6.0, DH parameters are negotiated following RFC7919.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>. Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>