

gnutls_anon_set_server_known_dh_params(3) gnutls gnutls_anon_set_server_known_dh_params(3)

NAME

gnutls_anon_set_server_known_dh_params - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_anon_set_server_known_dh_params(gnutls_anon_server_credentials_t res,  
gnutls_sec_param_t sec_param);
```

ARGUMENTS

gnutls_anon_server_credentials_t res
is a gnutls_anon_server_credentials_t type

gnutls_sec_param_t sec_param
is an option of the **gnutls_sec_param_t** enumeration

DESCRIPTION

This function will set the Diffie-Hellman parameters for an anonymous server to use. These parameters will be used in Anonymous Diffie-Hellman cipher suites and will be selected from the FFDHE set of RFC7919 according to the security level provided.

DEPRECATED

This function is unnecessary and discouraged on GnuTLS 3.6.0 or later. Since 3.6.0, DH parameters are negotiated following RFC7919.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.5.6

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

gnutls_anon_set_server_known_dh_params(3) gnutls gnutls_anon_set_server_known_dh_params(3)

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>