

NAME

gnutls_base64_decode2 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_base64_decode2(const gnutls_datum_t * base64, gnutls_datum_t * result);
```

ARGUMENTS

const gnutls_datum_t * base64
contains the encoded data

gnutls_datum_t * result
the location of decoded data

DESCRIPTION

This function will decode the given base64 encoded data. The decoded data will be allocated, and stored into result.

You should use **gnutls_free()** to free the returned data.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise an error code is returned.

SINCE

3.6.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_base64_decode2(3)

gnutls

gnutls_base64_decode2(3)

<https://www.gnutls.org/manual/>

gnutls

3.8.5

gnutls_base64_decode2(3)