

NAME

gnutls_certificate_get_ocsp_expiration - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
time_t gnutls_certificate_get_ocsp_expiration(gnutls_certificate_credentials_t sc, unsigned idx, int oidx, unsigned flags);
```

ARGUMENTS

gnutls_certificate_credentials_t sc
is a credentials structure.

unsigned idx is a certificate chain index as returned by **gnutls_certificate_set_key()** and friends

int oidx is an OCSP response index

unsigned flags
should be zero

DESCRIPTION

This function returns the validity of the loaded OCSP responses, to provide information on when to reload/refresh them.

Note that the credentials structure should be read-only when in use, thus when reloading, either the credentials structure must not be in use by any sessions, or a new credentials structure should be allocated for new sessions.

When *oidx* is (-1) then the minimum refresh time for all responses is returned. Otherwise the index specifies the response corresponding to the *oidx* certificate in the certificate chain.

RETURNS

On success, the expiration time of the OCSP response. Otherwise (time_t)(-1) on error, or (time_t)-2 on out of bounds.

SINCE

3.6.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>