

## NAME

gnutls\_certificate\_get\_ours - API function

## SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
const gnutls_datum_t * gnutls_certificate_get_ours(gnutls_session_t session);
```

## ARGUMENTS

gnutls\_session\_t session  
is a gnutls session

## DESCRIPTION

Gets the certificate as sent to the peer in the last handshake. The certificate is in raw (DER) format. No certificate list is being returned. Only the first certificate.

This function returns the certificate that was sent in the current handshake. In subsequent resumed sessions this function will return **NULL**. That differs from **gnutls\_certificate\_get\_peers()** which always returns the peer's certificate used in the original session.

## RETURNS

a pointer to a **gnutls\_datum\_t** containing our certificate, or **NULL** in case of an error or if no certificate was used.

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>