

**NAME**

gnutls\_certificate\_get\_peers - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
const gnutls_datum_t * gnutls_certificate_get_peers(gnutls_session_t session, unsigned int * list_size);
```

**ARGUMENTS**

gnutls\_session\_t session  
is a gnutls session

unsigned int \* list\_size  
is the length of the certificate list (may be **NULL**)

**DESCRIPTION**

Get the peer's raw certificate (chain) as sent by the peer. These certificates are in raw format (DER encoded for X.509). In case of a X.509 then a certificate list may be present. The list is provided as sent by the server; the server must send as first certificate in the list its own certificate, following the issuer's certificate, then the issuer's issuer etc. However, there are servers which violate this principle and thus on certain occasions this may be an unsorted list.

In resumed sessions, this function will return the peer's certificate list as used in the first/original session.

**RETURNS**

a pointer to a **gnutls\_datum\_t** containing the peer's certificates, or **NULL** in case of an error or if no certificate was used.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>