

NAME

gnutls_certificate_set_key - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_certificate_set_key(gnutls_certificate_credentials_t res, const char ** names, int names_size,  
gnutls_pcert_st * pcert_list, int pcert_list_size, gnutls_privkey_t key);
```

ARGUMENTS

gnutls_certificate_credentials_t *res*

is a **gnutls_certificate_credentials_t** type.

const char ** *names*

is an array of DNS names belonging to the public-key (NULL if none)

int *names_size*

holds the size of the names list

gnutls_pcert_st * *pcert_list*

contains a certificate list (chain) or raw public-key

int *pcert_list_size*

holds the size of the certificate list

gnutls_privkey_t *key*

is a **gnutls_privkey_t** key corresponding to the first public-key in *pcert_list*

DESCRIPTION

This function sets a public/private key pair in the `gnutls_certificate_credentials_t` type. The given public key may be encapsulated in a certificate or can be given as a raw key. This function may be called more than once, in case multiple key pairs exist for the server. For clients that want to send more than their own end- entity certificate (e.g., also an intermediate CA cert), the full certificate chain must be provided in *pcert_list*.

Note that the *key* will become part of the credentials structure and must not be deallocated. It will be automatically deallocated when the *res* structure is deinitialized.

If this function fails, the *res* structure is at an undefined state and it must not be reused to load other keys or certificates.

Note that, this function by default returns zero on success and a negative value on error. Since 3.5.6, when the flag **GNUTLS_CERTIFICATE_API_V2** is set using **gnutls_certificate_set_flags()** it returns an index (greater or equal to zero). That index can be used for other functions to refer to the added key-pair.

Since GnuTLS 3.6.6 this function also handles raw public keys.

RETURNS

On success this functions returns zero, and otherwise a negative value on error (see above for modifying that behavior).

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>