

gnutls_certificate_set_params_function(3) gnutls gnutls_certificate_set_params_function(3)

NAME

gnutls_certificate_set_params_function - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_certificate_set_params_function(gnutls_certificate_credentials_t        res,  
gnutls_params_function * func);
```

ARGUMENTS

gnutls_certificate_credentials_t *res*
is a gnutls_certificate_credentials_t type

gnutls_params_function * *func*
is the function to be called

DESCRIPTION

This function will set a callback in order for the server to get the Diffie-Hellman or RSA parameters for certificate authentication. The callback should return **GNUTLS_E_SUCCESS** (0) on success.

DEPRECATED

This function is unnecessary and discouraged on GnuTLS 3.6.0 or later. Since 3.6.0, DH parameters are negotiated following RFC7919.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>