

NAME

gnutls_certificate_set_x509_trust_file - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_certificate_set_x509_trust_file(gnutls_certificate_credentials_t cred, const char * cafile,  
gnutls_x509 crt_fmt_t type);
```

ARGUMENTS

gnutls_certificate_credentials_t cred
is a **gnutls_certificate_credentials_t** type.

const char * cafile
is a file containing the list of trusted CAs (DER or PEM list)

gnutls_x509 crt_fmt_t type
is PEM or DER

DESCRIPTION

This function adds the trusted CAs in order to verify client or server certificates. In case of a client this is not required to be called if the certificates are not verified using **gnutls_certificate_verify_peers2()**. This function may be called multiple times.

In case of a server the names of the CAs set here will be sent to the client if a certificate request is sent. This can be disabled using **gnutls_certificate_send_x509_rdn_sequence()**.

This function can also accept URLs. In that case it will import all certificates that are marked as trusted. Note that the supported URLs are the ones indicated by **gnutls_url_is_supported()**.

RETURNS

the number of certificates processed

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>