

NAME

gnutls_dh_params_import_pkcs3 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_dh_params_import_pkcs3(gnutls_dh_params_t params, const gnutls_datum_t *
pkcs3_params, gnutls_x509_cert_fmt_t format);
```

ARGUMENTS

gnutls_dh_params_t params

The parameters

const gnutls_datum_t * pkcs3_params

should contain a PKCS3 DHParams structure PEM or DER encoded

gnutls_x509_cert_fmt_t format

the format of params. PEM or DER.

DESCRIPTION

This function will extract the DHParams found in a PKCS3 formatted structure. This is the format generated by "openssl dhparam" tool.

If the structure is PEM encoded, it should have a header of "BEGIN DH PARAMETERS".

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>