

NAME

gnutls_dh_params_import_raw2 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_dh_params_import_raw2(gnutls_dh_params_t dh_params, const gnutls_datum_t * prime,  
                                const gnutls_datum_t * generator, unsigned key_bits);
```

ARGUMENTS

gnutls_dh_params_t dh_params

The parameters

const gnutls_datum_t * prime

holds the new prime

const gnutls_datum_t * generator

holds the new generator

unsigned key_bits

the private key bits (set to zero when unknown)

DESCRIPTION

This function will replace the pair of prime and generator for use in the Diffie-Hellman key exchange. The new parameters should be stored in the appropriate gnutls_datum.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

gnutls_dh_params_import_raw2(3)

gnutls

gnutls_dh_params_import_raw2(3)

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>