

**NAME**

gnutls\_dh\_params\_import\_raw3 - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
int gnutls_dh_params_import_raw3(gnutls_dh_params_t dh_params, const gnutls_datum_t * prime,  
const gnutls_datum_t * q, const gnutls_datum_t * generator);
```

**ARGUMENTS**

gnutls\_dh\_params\_t dh\_params

The parameters

const gnutls\_datum\_t \* prime

holds the new prime

const gnutls\_datum\_t \* q

holds the subgroup if available, otherwise NULL

const gnutls\_datum\_t \* generator

holds the new generator

**DESCRIPTION**

This function will replace the pair of prime and generator for use in the Diffie-Hellman key exchange. The new parameters should be stored in the appropriate gnutls\_datum.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error code is returned.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>