gnutls

#### **NAME**

```
gnutls_encode_ber_digest_info - API function
```

### **SYNOPSIS**

#include <gnutls/crypto.h>

int gnutls\_encode\_ber\_digest\_info(gnutls\_digest\_algorithm\_t hash, const gnutls\_datum\_t \* digest, gnutls\_datum\_t \* output);

## **ARGUMENTS**

```
gnutls_digest_algorithm_t hash
the hash algorithm that was used to get the digest

const gnutls_datum_t * digest
must contain the digest data

gnutls_datum_t * output
will contain the allocated DigestInfo BER encoded data
```

#### DESCRIPTION

This function will encode the provided digest data, and its algorithm into an RSA PKCS1 1.5 DigestInfo structure.

## **RETURNS**

On success, GNUTLS\_E\_SUCCESS (0) is returned, otherwise an error code is returned.

# **SINCE**

3.5.0

### REPORTING BUGS

Report bugs to <bugs@gnutls.org>.<br/>Home page: https://www.gnutls.org

# **COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

### **SEE ALSO**

gnutls

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/directory does not contain the HTML form visit

https://www.gnutls.org/manual/