

**NAME**

gnutls\_fips140\_pop\_context - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
int gnutls_fips140_pop_context( void);
```

**ARGUMENTS**

void

**DESCRIPTION**

Dissociate the FIPS context currently active on the current thread, reverting to the previously active context. If a cryptographic operation is ongoing in the current thread, e.g., **gnutls\_aead\_cipher\_init()** is called but **gnutls\_aead\_cipher\_deinit()** is not yet called, it returns an error **GNUTLS\_E\_INVALID\_REQUEST**.

This function is no-op if FIPS140 is not compiled in nor enabled at run-time.

**RETURNS**

0 upon success, a negative error code otherwise

**SINCE**

3.7.3

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>